



BEARING DE MEXICO, S.A. DE C.V.



6007lu Bearing 2D drawings and 3D CAD models

35,000 mm x 62,000 mm x 14,000 mm NTN 6007lu Sleeve Bearings

Bearing No. 6007lu

Size	35x62x14 mm
Bore Diameter	35,000 mm
Outer Diameter	62,000 mm
Width	14,000 mm
d	35,000 mm
D	62,000 mm
B	14,000 mm
C	14,000 mm
rs min	1 mm
Radial clearance class	CN
Mass	0.16 kg
Dynamic load, C	16 kN
Static load, C0	10.3 kN
Fatigue limit load, Cu	0.47 kN
f0	14.8
Nlim (grease)	6,800 rpm
Min operating temperature, Tmin	-25 ° C
Max operating temperature, Tmax	110 ° C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.95 Hz
Characteristic outer ring frequency, BPF0	4.6 Hz
Characteristic inner ring	6.4 Hz



BEARING DE MEXICO, S.A. DE C.V.

frequency, BPFI	
da min	40 mm
da max	42 mm
Da max	57 mm
ra max	1 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.145
EAN	4547359328363
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	35MM Bore; 62MM Outside Diameter; 14MM Outer Race Diameter; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing



BEARING DE MEXICO,S.A.DE C.V.

Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6007LU
Weight / LBS	0.32
Outer Race Width	0.551 Inch 14 Millimeter
Bore	1.378 Inch 35 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
bore diameter:	35 mm
precision rating:	ISO Class 0
outside diameter:	62 mm
finish/coating:	Uncoated
overall width:	14 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Single Seal
inner ring width:	14 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	14 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	6800 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	14000 RPM
dynamic load capacity:	16000 N
series:	60
static load capacity:	10300 N
manufacturer product page:	Click here